

The `atveryend` package

Heiko Oberdiek*
<heiko.oberdiek at googlemail.com>

2016/05/16 v1.9

Abstract

This L^AT_EX package provides two hooks for `\end{document}` that are executed after the hook of `\AtEndDocument`. `\AfterLastShipout` can be used for code that is to be executed right after the last `\clearpage` before the `.aux` file is closed. `\AtVeryEndDocument` is used for code after closing and final reading of the `.aux` file.

Contents

1 Documentation	2
1.1 Related work	3
2 Implementation	3
2.1 Tools	4
2.2 Hooks	4
2.3 Redefining <code>\enddocument</code>	6
2.3.1 L ^A T _E X kernel	6
2.3.2 L ^A T _E X kernel 2011/06/27	8
2.3.3 Package booklet, file <code>2up.tex</code>	9
2.3.4 Class <code>dinbrief</code>	9
2.3.5 Class <code>combine</code>	10
2.3.6 Class <code>jpsj2</code>	12
2.3.7 Testing and redefining	13
2.4 Hack into <code>\enddocument</code>	14
2.5 Using hooks of other packages	15
2.5.1 Package <code>scrfile</code>	15
2.5.2 Package <code>etoolbox</code>	15
2.6 Class <code>letter</code>	15
3 Test	17
3.1 Catcode checks for loading	17
4 Installation	19
4.1 Download	19
4.2 Bundle installation	19
4.3 Package installation	19
4.4 Refresh file name databases	20
4.5 Some details for the interested	20

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

5 Catalogue	20
6 Acknowledgement	21
7 References	21
8 History	21
[2009/12/06 v1.0]	21
[2009/12/07 v1.1]	21
[2009/12/09 v1.2]	22
[2009/12/11 v1.3]	22
[2010/01/25 v1.4]	22
[2010/03/24 v1.5]	22
[2011/04/15 v1.6]	22
[2011/04/23 v1.7]	22
[2011/06/30 v1.8]	22
[2016/05/16 v1.9]	22
9 Index	22

1 Documentation

There are packages (e.g. `hyperref` [4], `lastpage` [6]) that want to call code after the typesetting is done, for example to remember the last page number. L^AT_EX provides the hook `\AtEndDocument` (`clsguide` [1]). There are packages that use this hook to do their job for typesetting pages (e.g. `endfloat` emits the floats here [2]). Also a user might provide additional code in `\AtEndDocument`. Therefore packages have to call `\clearpage` in `\AtEndDocument` to get after the last shipout page. But this is not too reliable, because the right timing is important between packages that want or have to do things before the last page is output and packages that only work properly if they can reach the point after the last shipout.

Therefore the task of this package is to provide additional hooks for `\end{document}`. All hooks are called after the hook of `\AtEndDocument`.

`\BeforeClearDocument {\langle code \rangle}`

The code is called before the final `\clearpage` in `\enddocument`. However it is unknown, whether the last page is already shipped out or if this will be triggered by the final `\clearpage`.

`\AfterLastShipout {\langle code \rangle}`

The code is called after the final `\clearpage` of `\enddocument` before the main `.aux` file is closed. This is the right place to remember the last page in the `.aux` file, for instance.

`\AtVeryEndDocument {\langle code \rangle}`

The code is called after the `.aux` file is closed and read in again. It is the place for final checks, rerun hints, final messages.

```
\AtEndAfterFileList {\langle code\rangle}
```

After the .aux file closing and reading L^AT_EX prints the file list if requested by \listfiles. Then this hook is executed.

```
\AtVeryVeryEnd {\langle code\rangle}
```

This code is called right before the final \@@end.

1.1 Related work

Package `scrfile`: Markus Kohm has written package `scrfile` (part of KOMA-Script [5]) that provides hooks \BeforeClosingMainAux and after \AfterReadingMainAux. They have the same function as the hooks of this package. In fact this package uses them, if they are available.

Class `revtex4-1`: This class calls \clear@document in \enddocument that wraps the final call of \clearpage. Thus it can be used as hook to call stuff after that \clearpage. This is also done by this package.

Package `etoolbox`: It provides \AfterEndDocument, a hook right before \deadcycles or \@@end [3].

This package tries to combine as many approaches as possible:

- It looks for a known \enddocument and redefines it.
- Hooks that are provided by others are used (package `scrfile` or class `revtex4-1`).
- It redefines \checkend and \odofilelist to insert the hooks similar to package `scrfile`.
- The hook execution is wrapped in a macro that is redefined by its first call to prevent calling the hook more than once.

2 Implementation

```
1 (*package)
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3   \catcode13=5 % ^M
4   \endlinechar=13 %
5   \catcode123=1 %
6   \catcode125=2 %
7   \catcode64=11 %
8   \def\x{\endgroup
9     \expandafter\edef\csname AtVeryEnd@AtEnd\endcsname{%
10       \endlinechar=\the\endlinechar\relax
11       \catcode13=\the\catcode13\relax
12       \catcode32=\the\catcode32\relax
13       \catcode35=\the\catcode35\relax
14       \catcode61=\the\catcode61\relax
15       \catcode64=\the\catcode64\relax
16       \catcode123=\the\catcode123\relax
17       \catcode125=\the\catcode125\relax
18     }%
19   }%
```

```

20 \x\catcode61\catcode48\catcode32=10\relax%
21 \catcode13=5 % ^M
22 \endlinechar=13 %
23 \catcode35=6 % #
24 \catcode64=11 % @
25 \catcode123=1 % {
26 \catcode125=2 % }
27 \def\TMP@EnsureCode#1#2{%
28   \edef\AtVeryEnd@AtEnd{%
29     \AtVeryEnd@AtEnd
30     \catcode#1=\the\catcode#1\relax
31   }%
32   \catcode#1=#2\relax
33 }%
34 \TMP@EnsureCode{9}{10}%
35 \TMP@EnsureCode{39}{12}%
36 \TMP@EnsureCode{40}{12}%
37 \TMP@EnsureCode{41}{12}%
38 \TMP@EnsureCode{42}{12}%
39 \TMP@EnsureCode{45}{12}%
40 \TMP@EnsureCode{46}{12}%
41 \TMP@EnsureCode{47}{12}%
42 \TMP@EnsureCode{62}{12}%
43 \TMP@EnsureCode{91}{12}%
44 \TMP@EnsureCode{93}{12}%
45 \TMP@EnsureCode{96}{12}%
46 \edef\AtVeryEnd@AtEnd{\AtVeryEnd@AtEnd\noexpand\endinput}

    Package identification.
47 \NeedsTeXFormat{LaTeX2e}
48 \ProvidesPackage{atveryend}%
49 [2016/05/16 v1.9 Hooks at the very end of document (HO)]

```

2.1 Tools

```
\AtVeryEnd@ifundefined
50 \def\AtVeryEnd@ifundefined#1{%
51   \begingroup\expandafter\expandafter\expandafter\endgroup
52   \expandafter\ifx\csname #1\endcsname\relax
53   \expandafter\@firstoftwo
54   \else
55   \expandafter\@secondoftwo
56   \fi
57 }
```

2.2 Hooks

```
/veryEnd@BeforeClearDocumentHook
58 \let\AtVeryEnd@BeforeClearDocumentHook\empty

\AtVeryEnd@AfterLastShipoutHook
59 \let\AtVeryEnd@AfterLastShipoutHook\empty

\AtVeryEnd@AtVeryEndDocumentHook
60 \let\AtVeryEnd@AtVeryEndDocumentHook\empty

\VeryEnd@AtEndAfterFileListHook
61 \let\AtVeryEnd@AtEndAfterFileListHook\empty
```

```

\AtVeryEnd@AtVeryVeryEndHook
62 \let\AtVeryEnd@AtVeryVeryEndHook\@empty

\BeforeClearDocument
63 \newcommand*{\BeforeClearDocument}{%
64   \g@addto@macro\AtVeryEnd@BeforeClearDocumentHook
65 }

\AfterLastShipout
66 \newcommand*{\AfterLastShipout}{%
67   \g@addto@macro\AtVeryEnd@AfterLastShipoutHook
68 }

\AtVeryEndDocument
69 \newcommand*{\AtVeryEndDocument}{%
70   \g@addto@macro\AtVeryEnd@AtVeryEndDocumentHook
71 }

\AtEndAfterFileList
72 \newcommand*{\AtEndAfterFileList}{%
73   \g@addto@macro\AtVeryEnd@AtEndAfterFileListHook
74 }

\AtVeryVeryEnd
75 \newcommand*{\AtVeryVeryEnd}{%
76   \g@addto@macro\AtVeryEnd@AtVeryVeryEndHook
77 }

\Call@BeforeClearDocument
78 \newcommand*{\Call@BeforeClearDocument}{%
79   \let\BeforeClearDocument\@firstofone
80   \ifx\AtVeryEnd@BeforeClearDocumentHook\@empty
81     \PackageInfo{atveryend}{Empty hook 'BeforeClearDocument'}%
82   \else
83     \PackageInfo{atveryend}{Executing hook 'BeforeClearDocument'}%
84     \AtVeryEnd@BeforeClearDocumentHook
85   \fi
86   \global\let\AtVeryEnd@BeforeClearDocumentHook\@undefined
87   \global\let\Call@BeforeClearDocument\relax
88 }

\Call@AfterLastShipout
89 \newcommand*{\Call@AfterLastShipout}{%
90   \let\AfterLastShipout\@firstofone
91   \ifx\AtVeryEnd@AfterLastShipoutHook\@empty
92     \PackageInfo{atveryend}{Empty hook 'AfterLastShipout'}%
93   \else
94     \PackageInfo{atveryend}{Executing hook 'AfterLastShipout'}%
95     \AtVeryEnd@AfterLastShipoutHook
96   \fi
97   \global\let\AtVeryEnd@AfterLastShipoutHook\@undefined
98   \global\let\Call@AfterLastShipout\relax
99 }

\Call@AtVeryEndDocument
100 \newcommand*{\Call@AtVeryEndDocument}{%
101   \let\AtVeryEndDocument\@firstofone

```

```

102  \ifx\AtVeryEnd@AtVeryEndDocumentHook\@empty
103    \PackageInfo{atveryend}{Empty hook 'AtVeryEndDocument'}%
104  \else
105    \PackageInfo{atveryend}{Executing hook 'AtVeryEndDocument'}%
106    \AtVeryEnd@AtVeryEndDocumentHook
107  \fi
108  \global\let\AtVeryEnd@AtVeryEndDocumentHook\@undefined
109  \global\let\Call@AtVeryEndDocument\relax
110 }

\Call@AtEndAfterFileList

111 \newcommand*{\Call@AtEndAfterFileList}{%
112   \Call@AtVeryEndDocument
113   \let\AtEndAfterFileList\@firstofone
114   \ifx\AtVeryEnd@AtEndAfterFileListHook\@empty
115     \PackageInfo{atveryend}{Empty hook 'AtEndAfterFileList'}%
116   \else
117     \PackageInfo{atveryend}{Executing hook 'AtEndAfterFileList'}%
118     \AtVeryEnd@AtEndAfterFileListHook
119   \fi
120   \global\let\AtVeryEnd@AtEndAfterFileListHook\@undefined
121   \global\let\Call@AtEndAfterFileList\relax
122 }

\Call@AtVeryVeryEnd

123 \newcommand*{\Call@AtVeryVeryEnd}{%
124   \Call@AtEndAfterFileList
125   \let\AtVeryVeryEnd\@firstofone
126   \ifx\AtVeryEnd@AtVeryVeryEndHook\@empty
127     \PackageInfo{atveryend}{Empty hook 'AtVeryVeryEnd'}%
128   \else
129     \PackageInfo{atveryend}{Executing hook 'AtVeryVeryEnd'}%
130     \AtVeryEnd@AtVeryVeryEndHook
131   \fi
132   \global\let\AtVeryEnd@AtVeryVeryEndHook\@undefined
133   \global\let\Call@AtVeryVeryEnd\relax
134 }

```

2.3 Redefining \enddocument

This approach looks for known versions of `\enddocument` and redefines it. Class `seminar` and package `slidesec` are not checked, because there would be too much combinations to check.

2.3.1 L^AT_EX kernel

```

\AtVeryEnd@test@standard

135 \def\AtVeryEnd@test@standard{%
136   \let\AtEndDocument\@firstofone
137   \enddocumenthook
138   \checkend{document}%
139   \clearpage
140   \begingroup
141     \if@filesw
142       \immediate\closeout\mainaux
143       \let\@setckpt\gobbletwo
144       \let\@newl@bel\testdef

```

```

145      \tempswafalse
146      \makeatletter
147      \input\jobname.aux %
148  \fi
149  \odofilelist
150  \ifdim \font@submax >\fontsubfuzz\relax
151      \@font@warning{Size substitutions with differences\MessageBreak
152                      up to \font@submax\space have occurred.\@gobbletwo}%
153  \fi
154  \defaultsubs
155  \refundefined
156  \if@filesw
157      \ifx \multiplelabels \relax
158          \if@tempswa
159              \@latex@warning@no@line{Label(s) may have changed. %
160              Rerun to get cross-references right}%
161          \fi
162      \else
163          \multiplelabels
164      \fi
165  \fi
166  \endgroup
167  \deadcycles\z@
168  \@@end
169 }

\AtVeryEnd@enddocument@standard
170 \def\AtVeryEnd@enddocument@standard{%
171     \let\AtEndDocument\@firstofone
172     \enddocumenthook
173     \checkend{document}%
174     \Call@BeforeClearDocument
175     \clearpage
176     \Call@AfterLastShipout
177     \begingroup
178     \if@filesw
179         \immediate\closeout\mainaux
180         \let\@setckpt\@gobbletwo
181         \let\@newl@bel\@testdef
182         \tempswafalse
183         \makeatletter
184         \input\jobname.aux %
185     \fi
186     \Call@AtVeryEndDocument
187     \odofilelist
188     \Call@AtEndAfterFileList
189     \ifdim \font@submax >\fontsubfuzz\relax
190         \@font@warning{Size substitutions with differences\MessageBreak
191                     up to \font@submax\space have occurred.\@gobbletwo}%
192     \fi
193     \defaultsubs
194     \refundefined
195     \if@filesw
196         \ifx \multiplelabels \relax
197             \if@tempswa
198                 \@latex@warning@no@line{Label(s) may have changed. %
199                 Rerun to get cross-references right}%
200             \fi

```

```

201      \else
202          \@multiplelabels
203      \fi
204  \fi
205 \endgroup
206 \deadcycles{z}
207 \CallAtVeryVeryEnd
208 \@@end
209 }

```

2.3.2 L^AT_EX kernel 2011/06/27

The L^AT_EX 2 _{ε} release 2011/06/27 has changed `\enddocument` (`\input` is replaced by `\@@input`).

AtVeryEnd@test@standard20110627

```

210 \expandafter\def\csname AtVeryEnd@test@standard20110627\endcsname{%
211   \let\AtEndDocument\@firstofone
212   \enddocumenthook
213   \checkend{document}%
214   \clearpage
215   \begingroup
216     \if@filesw
217       \immediate\closeout\mainaux
218       \let\@setckpt\gobbletwo
219       \let\@newl@bel\testdef
220       \tempswafalse
221       \makeatletter
222       \@@input\jobname.aux %
223     \fi
224   \odofilelist
225   \ifdim \font@submax >\fontsubfuzz\relax
226     \font@warning{Size substitutions with differences\MessageBreak
227                   up to \font@submax\space have occurred.\gobbletwo}%
228   \fi
229   \defaultsubs
230   \refundefined
231   \if@filesw
232     \ifx \multiplelabels \relax
233       \if@tempswa
234         \@latex@warning{no@line{Label(s) may have changed. %
235                           Rerun to get cross-references right}%
236       \fi
237     \else
238       \multiplelabels
239     \fi
240   \fi
241   \endgroup
242   \deadcycles{z}
243   \@@end
244 }

```

nd@enddocument@standard20110627

```

245 \expandafter\def\csname AtVeryEnd@enddocument@standard20110627\endcsname{%
246   \let\AtEndDocument\@firstofone
247   \enddocumenthook
248   \checkend{document}%
249   \CallBeforeClearDocument

```

```

250 \clearpage
251 \Call@AfterLastShipout
252 \begingroup
253   \if@filesw
254     \immediate\closeout\mainaux
255     \let\setckpt\gobbletwo
256     \let\newl@bel\testdef
257     \tempswafalse
258     \makeatletter
259     \@@input{jobname.aux}%
260   \fi
261 \Call@AtVeryEndDocument
262 \dofilelist
263 \Call@AtEndAfterFileList
264 \ifdim \font@submax > \fontsubfuzz \relax
265   \font@warning{Size substitutions with differences\MessageBreak
266     up to \font@submax\space have occurred.\gobbletwo}%
267 \fi
268 \defaultsubs
269 \refundefined
270 \if@filesw
271   \ifx \multiplelabels \relax
272     \if@tempswa
273       \@latex@warning{no@line{Label(s) may have changed. %
274         Rerun to get cross-references right}}%
275     \fi
276   \else
277     \multiplelabels
278   \fi
279 \fi
280 \endgroup
281 \deadcycles{z}
282 \Call@AtVeryVeryEnd
283 \@@end
284 }

```

2.3.3 Package **booklet**, file **2up.tex**

```

\AtVeryEnd@test@booklet
285 \expandafter\def\expandafter\AtVeryEnd@test@booklet\expandafter{%
286   \expandafter\twoupclearpage
287   \AtVeryEnd@test@standard
288 }

\AtVeryEnd@enddocument@booklet
289 \expandafter\def\expandafter\AtVeryEnd@enddocument@booklet\expandafter{%
290   \expandafter\twoclearpage
291   \AtVeryEnd@enddocument@standard
292 }

```

2.3.4 Class **dinbrief**

```

\AtVeryEnd@test@dinbrief
293 \def\AtVeryEnd@test@dinbrief{%
294   \checkend{document}%
295   \newpage
296   \begingroup
297   \if@filesw

```

```

298      \ifnum\c@labelgen>0 %
299          \immediate\closeout\@mainlbl
300          \makeatletter
301          \input \jobname@lbl\relax
302          \clearpage
303      \fi
304      \immediate\closeout\@mainaux
305  \fi
306 \endgroup
307 \deadcycles\z@
308 \@@end
309 }

\AtVeryEnd@enddocument@dinbrief

310 \def\AtVeryEnd@enddocument@dinbrief{%
311   \checkend{document}%
312   \Call@BeforeClearDocument
313   \newpage
314   \Call@AfterLastShipout
315   \begingroup
316     \if@filesw
317       \ifnum\c@labelgen>\z@
318           \immediate\closeout\@mainlbl
319           \makeatletter
320           \input \jobname@lbl\relax
321           \clearpage
322       \fi
323       \immediate\closeout\@mainaux
324   \fi
325   \Call@AtVeryEndDocument
326   \csname \dofilelist\endcsname
327   \Call@AtEndAfterFileList
328 \endgroup
329 \deadcycles\z@
330 \Call@AtVeryVeryEnd
331 \@@end
332 }

```

2.3.5 Class **combine**

```

\AtVeryEnd@test@combine

333 \def\AtVeryEnd@test@combine{%
334   \enddocumenthook
335   \checkend{document}%
336   \clearpage
337   \begingroup
338     \if@filesw
339       \immediate\closeout\@mainaux
340       \immediate\closeout\@partaux
341       \let\@setckpt\gobbletwo
342       \let\@newl@bel\testdef
343       \tempswafalse
344       \makeatletter \input\c@lmainauxfile %% change here
345     \fi
346     \c@lenddoca %% a replacement
347     \refundefined
348   \endgroup
349   \deadcycles\z@

```

```

350  \@@end
351 }

\AtVeryEnd@enddocument@combine

352 \def\AtVeryEnd@enddocument@combine{%
353   \enddocumenthook
354   \checkend{document}%
355   \Call@BeforeClearDocument
356   \clearpage
357   \Call@AfterLastShipout
358   \begingroup
359     \if@filesw
360       \immediate\closeout\mainaux
361       \immediate\closeout\partaux
362       \let\@setckpt\gobbletwo
363       \let\@newl@bel\@testdef
364       \tempswfalse
365       \makeatletter \input\c@lmainauxfile %% change here
366     \fi
367   \Call@AtVeryEndDocument
368   \c@lenddoca %% a replacement
369   \refundefined
370   \endgroup
371   \deadcycles{z@}
372   \Call@AtVeryVeryEnd
373   \@@end
374 }

\AtVeryEnd@test@c@lenddoca

375 \long\def\AtVeryEnd@test@c@lenddoca{%
376   \dofilelist
377   \ifdim\font@submax>\fontsubfuzz\relax
378     \font@warning{%
379       Size substitutions with differences\MessageBreak
380       up to \font@submax\space have occurred.\gobbletwo
381     }%
382   \fi
383   \defaultsubs
384   \if@filesw
385     \ifx\multiplelabels\relax
386       \if@tempswa
387         \latext@warning{no@line}{%
388           Label(s) may have changed. %
389           Rerun to get cross-references right%
390         }%
391       \fi
392     \else
393       \multiplelabels
394     \fi
395   \fi
396 }

\c@lenddoca

397 \ifx\AtVeryEnd@c@lenddoca\c@lenddoca
398   \def\c@lenddoca{%
399     \dofilelist
400     \Call@AtEndAfterFileList
401     \ifdim\font@submax>\fontsubfuzz\relax

```

```

402      \@font@warning{%
403          Size substitutions with differences\MessageBreak
404          up to \font@submax\space have occured.\@gobbletwo
405      }%
406      \fi
407      \@defaultsubs
408      \if@filesw
409          \ifx\@multiplelabels\relax
410              \if@tempswa
411                  \@latex@warning@no@line{%
412                      Label(s) may have changed. %
413                      Rerun to get cross-references right%
414                  }%
415              \fi
416          \else
417              \@multiplelabels
418          \fi
419      \fi
420  }%
421 \fi

```

2.3.6 Class **jpsj2**

```

\AtVeryEnd@test@jpsj
422 \def\AtVeryEnd@test@jpsj{%
423   \if@lastpagebalancing
424     \global\let\outputdblcol=\balancing@outputdblcol
425   \fi
426   \@checkend{document}%
427   \clearpage
428   \begingroup
429     \if@filesw
430       \immediate\closeout\mainaux
431       \def\global\@namedef##1##2{}%
432       \def\newlabel{\@testdef r}%
433       \def\bibcite{\@testdef b}%
434       \if@tempswafalse
435         \makeatletter
436         \input \jobname.aux %
437       \if@tempswa
438           \@warning{%
439               Label(s) may have changed. %
440               Rerun to get cross-references right%
441           }%
442       \fi
443     \fi
444   \endgroup
445   \deadcycles{z}%
446   \@@end
447 }

\AtVeryEnd@enddocument@jpsj
448 \def\AtVeryEnd@enddocument@jpsj{%
449   \if@lastpagebalancing
450     \global\let\outputdblcol=\balancing@outputdblcol
451   \fi
452   \@checkend{document}%
453   \Call{BeforeClearDocument}

```

```

454 \clearpage
455 \Call@AfterLastShipout
456 \begingroup
457   \if@filesw
458     \immediate\closeout\mainaux
459     \def\global\@namedef##1##2{}%
460     \def\newlabel{\@testdef r}%
461     \def\bibcite{\@testdef b}%
462     \c@tempswafalse
463     \makeatletter
464     \input \jobname.aux %
465   \if@tempswa
466     \c@warning{%
467       Label(s) may have changed. %
468       Rerun to get cross-references right%
469     }%
470   \fi
471 \fi
472 \Call@AtVeryEndDocument
473 \csname @ofilelist\endcsname
474 \Call@AtEndAfterFileList
475 \endgroup
476 \deadcycles\z@
477 \Call@AtVeryVeryEnd
478 \@@end
479 }

```

2.3.7 Testing and redefining

\AtVeryEnd@Test

```

480 \def\AtVeryEnd@Test#1#2{%
481   \expandafter\ifx\csname AtVeryEnd@test@#2\endcsname#1%
482     \expandafter\let\expandafter#1%
483     \csname AtVeryEnd@enddocument@#2\endcsname
484   \begingroup
485     \let\on@line\empty
486     \PackageInfo{atveryend}{%
487       \string#1 detected (#2)%
488     }%
489   \endgroup
490   \expandafter\AtVeryEnd@SkipToNil
491 \fi
492 }

```

\AtVeryEnd@SkipToNil

```
493 \def\AtVeryEnd@SkipToNil#1\@nil{}
```

\AtVeryEnd@RedefEndDocument

```

494 \def\AtVeryEnd@RedefEndDocument#1{%
495   \ifx#1\@undefined
496   \else
497     \AtVeryEnd@Test#1{standard20110627}%
498     \AtVeryEnd@Test#1{standard}%
499     \AtVeryEnd@Test#1{booklet}%
500     \AtVeryEnd@Test#1{dinbrief}%
501     \AtVeryEnd@Test#1{combine}%
502     \AtVeryEnd@Test#1{jpsj}%
503     \AtVeryEnd@SkipToNil

```

```

504      \@nil
505    \fi
506 }

507 \AtVeryEnd@RedefEndDocument\enddocument
508 \AtVeryEnd@RedefEndDocument\AP@enddocument % afterpage.sty
509 \AtVeryEnd@RedefEndDocument\hyper@back@cite@enddocument % htx-bc.sty
510 \AtVeryEnd@RedefEndDocument\hyper@enddocument % hyper.sty
511 \AtVeryEnd@RedefEndDocument\hyper@fn@enddocument % hyper.sty
512 \AtVeryEnd@RedefEndDocument\cweb@save@enddocument % cweb.cls
513 \AtVeryEnd@RedefEndDocument\prev@enddocument % flushend.sty
514 \AtVeryEnd@RedefEndDocument\endorigdocument % gaceta.cls
515 \AtVeryEnd@RedefEndDocument\keependdoc % aguplus.sty
516 \AtVeryEnd@RedefEndDocument\EMenddocument % t-angles.sty
517 \AtVeryEnd@RedefEndDocument\docmute@enddocument % docmute.sty
518 \AtVeryEnd@RedefEndDocument\@enddocument % alatex.sty
519 \AtVeryEnd@RedefEndDocument\enddocumentasusual % frenchle.sty
520 \AtVeryEnd@RedefEndDocument\old@enddocument % uwthesis.cls

```

2.4 Hack into \enddocument

```

521 \def\AtVeryEnd@document{document}%
522 \def\AtVeryEnd@RedefCheckEnd{%
523   \expandafter\def\expandafter@\checkend
524   \expandafter##\expandafter1\expandafter{%
525     \@checkend{##1}%
526     \def\AtVeryEnd@temp{##1}%
527     \ifx\AtVeryEnd@temp\AtVeryEnd@document
528       \let\AtVeryEnd@OrgClearpage\clearpage
529       \def\clearpage{%
530         \let\clearpage\AtVeryEnd@OrgClearpage
531         \Call@BeforeClearDocument
532         \clearpage
533         \Call@AfterLastShipout
534       }%
535     \fi
536   }%
537   \aftergroup\AtVeryEnd@RedefCheckEnd
538 }%
539 \AtBeginDocument{%
540   \AtEndDocument{%
541     \AtVeryEnd@RedefCheckEnd
542   }%
543 }

544 \AtEndDocument{%
545   \@ifundefined{@dofilelist}{%
546     \gdef\@dofilelist{%
547       \Call@AtVeryEndDocument
548       \Call@AtEndAfterFileList
549     }%
550   }{%
551     \begingroup
552     \toks@\expandafter{\@dofilelist}%
553     \xdef\@dofilelist{%
554       \noexpand\Call@AtVeryEndDocument
555       \the\toks@
556       \noexpand\Call@AtEndAfterFileList
557     }%

```

```

558     \endgroup
559 }
560 }

```

2.5 Using hooks of other packages

2.5.1 Package `scrlfile`

```

561 \AtBeginDocument{%
562   \@ifpackageloaded{scrlfile}{%
563     \AtVeryEnd@ifundefined{BeforeClosingMainAux}{}{%
564       \BeforeClosingMainAux{\Call@AfterLastShipout}%
565     }%
566     \AtVeryEnd@ifundefined{AfterReadingMainAux}{}{%
567       \AfterReadingMainAux{\Call@AtVeryEndDocument}%
568     }%
569   }{}%

```

2.5.2 Package `etoolbox`

```

570   \@ifpackageloaded{etoolbox}{%
571     \AtVeryEnd@ifundefined{AfterEndDocument}{}{%
572       \AfterEndDocument{\Call@AtVeryEndDocument}%
573     }%
574   }{}%
575 }

```

2.6 Class `letter`

The class `letter` and some similar classes insert material (`\@startlabels`) at the end of the document. However, this method violates a precondition of this package that the `\clearpage` in `\enddocument` is the final call with no material at later times. Therefore we move the label making from the `.aux` file to `\AtEndDocument`.

```

576 \def\AtVeryEnd@temp{%
577   \AtBeginDocument{%
578     \let\@startlabels\startlabels
579     \let\@mlabel\mlabel
580     \if@filesw
581       \immediate\write\@mainaux{\string\@startlabels}%
582     \fi
583   }%
584   \AtEndDocument{%
585     \if@filesw
586       \immediate\write\@mainaux{\string\clearpage}%
587     \fi
588   }%
589 }
590 \ifx\makelabels\AtVeryEnd@temp
591 \else
592   \expandafter\AtVeryEnd@AtEnd
593 \fi%
594 \let\AtVeryEnd@PatchLetter=N%
595 \begingroup\expandafter\expandafter\expandafter\expandafter\endgroup
596 \expandafter\ifx\csname endletter\endcsname\relax
597 \else
598   \long\def\AtVeryEnd@TestEndLetter#1@auxout#2#3\AtVeryEnd@Nil{%
599     \def\AtVeryEnd@temp{#2}%
600     \ifx\AtVeryEnd@temp\empty
601     \else
602       \onelevel@sanitize\AtVeryEnd@temp

```

```

603   \edef\AtVeryEnd@StringMlabel{%
604     \string\string
605     \string\@mlabel
606     \expandafter\@gobble\string\{%
607   }%
608   \def\AtVeryEnd@CatchFirst##1##2##3##4##5##6##7##8{%
609     ##1##2##3##4##5##6##7##8\AtVeryEnd@CatchSecond
610   }%
611   \def\AtVeryEnd@CatchSecond##1##2##3##4##5##6##7##8##9@nil{%
612     ##1##2##3##4##5##6##7##8%
613   }%
614   \edef\AtVeryEnd@temp{%
615     \expandafter\AtVeryEnd@CatchFirst\AtVeryEnd@temp
616     {}{}{}{}{}{}{}%
617     {}{}{}{}{}{}{}{}%
618     \@nil
619   }%
620   \ifx\AtVeryEnd@temp\AtVeryEnd@StringMlabel
621     \expandafter\def\expandafter\endletter\expandafter{%
622       \endletter
623       \begingroup
624         \let\\=\relax
625         \let\protect\@unexpandable@protect
626         \let\@mlabel=\relax
627         \edef\x{\endgroup
628           \noexpand\AtEndDocument{%
629             \@gobble#2%
630           }%
631         }%
632         \x
633       }%
634       \let\AtVeryEnd@PatchLetter=Y%
635     \fi
636   \fi
637 }%
638 \expandafter\AtVeryEnd@TestEndLetter\endletter
639 \auxout{}@VeryEnd@Nil
640 \fi
641 \ifx\AtVeryEnd@PatchLetter Y%
642   \begingroup
643     \let\on@line\empty
644     \PackageInfo{atveryend}{%
645       \@backslashchar makelabels detected. %
646       Moving labels\MessageBreak
647       from '.aux' file to \@backslashchar AtEndDocument%
648     }%
649   \endgroup
650   \def\makelabels{%
651     \AtBeginDocument{%
652       \let\@startlabels\startlabels
653       \let\@mlabel\mlabel
654     }%
655   }%
656   \AtEndDocument{%
657     \AtVeryEnd@ifundefined{@startlabels}{%
658     }{%
659       \clearpage
660       \@startlabels

```

```

661      }%
662      }%
663      \AfterLastShipout{%
664      \let\@startlabels\relax
665      \let\@mlabel\@gobbletwo
666      }%
667 \else
668   \PackageWarning{atveryend}{%
669     \@backslashchar makelabels detected, but labels cannot\MessageBreak
670     be moved to \@backslashchar AtEndDocument, because\MessageBreak
671     \@backslashchar endletter is not in expected form%
672   }%
673 \fi
674 \AtVeryEnd@AtEnd%
675 
```

3 Test

3.1 Catcode checks for loading

```

676 {*test1}
677 \catcode`\#=1 %
678 \catcode`\'=2 %
679 \catcode`\#=6 %
680 \catcode`\@=11 %
681 \expandafter\ifx\csname count@\endcsname\relax
682   \countdef\count@=255 %
683 \fi
684 \expandafter\ifx\csname @gobble\endcsname\relax
685   \long\def\@gobble#1{}%
686 \fi
687 \expandafter\ifx\csname @firstofone\endcsname\relax
688   \long\def\@firstofone#1{\#1}%
689 \fi
690 \expandafter\ifx\csname loop\endcsname\relax
691   \expandafter\@firstofone
692 \else
693   \expandafter\@gobble
694 \fi
695 {%
696   \def\loop#1\repeat{%
697     \def\body{#1}%
698     \iterate
699   }%
700   \def\iterate{%
701     \body
702     \let\next\iterate
703   \else
704     \let\next\relax
705   \fi
706   \next
707 }%
708   \let\repeat=\fi
709 }%
710 \def\RestoreCatcodes{}%
711 \count@=0 %
712 \loop

```

```

713 \edef\RestoreCatcodes{%
714   \RestoreCatcodes
715   \catcode\the\count@=\the\catcode\count@\relax
716 }%
717 \ifnum\count@<255 %
718   \advance\count@ 1 %
719 \repeat
720
721 \def\RangeCatcodeInvalid#1#2{%
722   \count@=#1\relax
723   \loop
724     \catcode\count@=15 %
725   \ifnum\count@<#2\relax
726     \advance\count@ 1 %
727   \repeat
728 }
729 \def\RangeCatcodeCheck#1#2#3{%
730   \count@=#1\relax
731   \loop
732     \ifnum#3=\catcode\count@
733     \else
734       \errmessage{%
735         Character \the\count@\space
736         with wrong catcode \the\catcode\count@\space
737         instead of \number#3%
738     }%
739   \fi
740   \ifnum\count@<#2\relax
741     \advance\count@ 1 %
742   \repeat
743 }
744 \def\space{ }
745 \expandafter\ifx\csname LoadCommand\endcsname\relax
746 \def\LoadCommand{\input atveryend.sty\relax}%
747 \fi
748 \def\Test{%
749   \RangeCatcodeInvalid{0}{47}%
750   \RangeCatcodeInvalid{58}{64}%
751   \RangeCatcodeInvalid{91}{96}%
752   \RangeCatcodeInvalid{123}{255}%
753   \catcode`\@=12 %
754   \catcode`\\=0 %
755   \catcode`\%=14 %
756   \LoadCommand
757   \RangeCatcodeCheck{0}{36}{15}%
758   \RangeCatcodeCheck{37}{37}{14}%
759   \RangeCatcodeCheck{38}{47}{15}%
760   \RangeCatcodeCheck{48}{57}{12}%
761   \RangeCatcodeCheck{58}{63}{15}%
762   \RangeCatcodeCheck{64}{64}{12}%
763   \RangeCatcodeCheck{65}{90}{11}%
764   \RangeCatcodeCheck{91}{91}{15}%
765   \RangeCatcodeCheck{92}{92}{0}%
766   \RangeCatcodeCheck{93}{96}{15}%
767   \RangeCatcodeCheck{97}{122}{11}%
768   \RangeCatcodeCheck{123}{255}{15}%
769   \RestoreCatcodes
770 }

```

```

771 \Test
772 \csname @@end\endcsname
773 \end
774 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/atveryend.dtx](http://ctan.org/pkg/atveryend) The source file.

[CTAN:macros/latex/contrib/oberdiek/atveryend.pdf](http://ctan.org/pkg/atveryend.pdf) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](http://ctan.org/install/macros/latex/contrib/oberdiek.tds.zip)

TDS refers to the standard “A Directory Structure for *T_EX* Files” ([CTAN:texmf/texmf.pdf](http://ctan.org/texmf/texmf.pdf)). Directories with *texmf* in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the *oberdiek.tds.zip* in the TDS tree (also known as *texmf* tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory *TDS:scripts/oberdiek/* for scripts that need further installation steps. Package *attachfile2* comes with the Perl script *pdfatfi.pl* that should be installed in such a way that it can be called as *pdfatfi*. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The *.dtx* file is a self-extracting *docstrip* archive. The files are extracted by running the *.dtx* through plain *T_EX*:

```
tex atveryend.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as *texmf* tree):

atveryend.sty	→ <i>tex/latex/oberdiek/atveryend.sty</i>
atveryend.pdf	→ <i>doc/latex/oberdiek/atveryend.pdf</i>
test/atveryend-test1.tex	→ <i>doc/latex/oberdiek/test/atveryend-test1.tex</i>
atveryend.dtx	→ <i>source/latex/oberdiek/atveryend.dtx</i>

If you have a *docstrip.cfg* that configures and enables *docstrip*’s TDS installing feature, then some files can already be in the right place, see the documentation of *docstrip*.

¹<http://ctan.org/pkg/atveryend>

4.4 Refresh file name databases

If your \TeX distribution (te \TeX , mik \TeX , ...) relies on file name databases, you must refresh these. For example, te \TeX users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk atveryend.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain \TeX : Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{atveryend.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX.

```
pdflatex atveryend.dtx
makeindex -s gind.ist atveryend.idx
pdflatex atveryend.dtx
makeindex -s gind.ist atveryend.idx
pdflatex atveryend.dtx
```

5 Catalogue

The following XML file can be used as source for the **TeX Catalogue**. The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `atveryend.xml`.

```
775 <catalogue>
776 <?xml version='1.0' encoding='us-ascii'?>
777 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
778 <entry datestamp='$Date$' modifier='$Author$' id='atveryend'>
779   <name>atveryend</name>
780   <caption>Hooks at the very end of a document.</caption>
781   <authorref id='auth:oberdiek' />
782   <copyright owner='Heiko Oberdiek' year='2009-2011' />
783   <license type='lppl1.3' />
784   <version number='1.9' />
785   <description>
786     This LaTeX packages provides two hooks for <tt>\end{document}</tt>
```

```

787      that are executed after the hook of <tt>\AtEndDocument</tt>:  

788      <tt>\AfterLastShipout</tt> can be used for code that is to be executed  

789      right after the last <tt>\clearpage</tt> before the '<tt>.aux</tt>' file  

790      is closed. <tt>\AtVeryEndDocument</tt> is used for code after closing  

791      and final reading of the '<tt>.aux</tt>' file.  

792      <p/>  

793      The package is part of the <xref refid='oberdiek'>oberdiek</xref> bundle.  

794      </description>  

795      <documentation details='Package documentation'  

796          href='ctan:/macros/latex/contrib/oberdiek/atveryend.pdf' />  

797      <ctan file='true' path='/macros/latex/contrib/oberdiek/atveryend.dtx' />  

798      <miktex location='oberdiek' />  

799      <texlive location='oberdiek' />  

800      <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />  

801  </entry>  

802 </catalogue>

```

6 Acknowledgement

Arthur Ogawa: He proposed the new API with \AfterLastShipout and gave me much feedback, comprehensive class/package lists, many suggestions and comments.

7 References

- [1] The L^AT_EX3 Project: *L^AT_EX2e for class and package writers* 2006/02/15; [CTAN: macros/latex/doc/clsguide.pdf](#).
- [2] James Darrell McCauley, Jeff Goldberg: *The endfloat package*; 1995/10/11 v2.4i; [CTAN:macros/latex/contrib/endfloat/endfloat.pdf](#).
- [3] Philipp Lehmann: *The etoolbox package*; 2009/08/06 v1.8; [CTAN:macros/latex/contrib/etoolbox/etoolbox.pdf](#).
- [4] Sebastian Rahtz, Heiko Oberdiek: *The hyperref package*; 2009/12/05 v6.79l; [CTAN:macros/latex/contrib/hyperref/](#).
- [5] Markus Kohm: *KOMA-Script*; 2009/07/24 v3.04a; <http://www.komascript.de/>.
- [6] Jeff Goldberg: *The lastpage package*; 1994/07/20 v0.1b; [CTAN:macros/latex/contrib/lastpage/lastpage.pdf](#).
- [7] APS, AIP, Arthur Orgawa; ReVTeX 4.1; 2009/10/13 v4.1; <http://authors.aps.org/revtex4/>.

8 History

[2009/12/06 v1.0]

- The first version.

[2009/12/07 v1.1]

- Bug fixes.

[2009/12/09 v1.2]

- Additional support of classes and packages.

[2009/12/11 v1.3]

- Patch for letter like classes that puts label into the ‘.aux’ file.
- Hook `\BeforeClearDocument` added (request from Arthur Ogawa).
- Patch of `\clear@document` removed (Arthur Ogawa).
- A nested `\AtBeginDocument` removed.

[2010/01/25 v1.4]

- Moved from TDS:*/generic/* to TDS:*/latex/*.

[2010/03/24 v1.5]

- `\Call@BeforeClearDocument` fixed (Ahmed Musa).

[2011/04/15 v1.6]

- `\Call@AtEndAfterFileList` and `\Call@AtVeryVeryEnd` added.

[2011/04/23 v1.7]

- Some fix for `\AtVeryEnd@RedefCheckEnd` to avoid error because of undefined control sequence in some circumstances (thanks to D.P. Story for bug report).

[2011/06/30 v1.8]

- Support of changed `\enddocument` of L^AT_EX 2_& 2011/06/27.

[2016/05/16 v1.9]

- Documentation updates.

9 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\#</code>	679
<code>\%</code>	755
<code>\@</code>	680, 753
<code>\@end</code>	168, 208, 243, 283, 308, 331, 350, 373, 446, 478
<code>\@input</code>	222, 259
<code>\auxout</code>	598, 639
<code>\backslashchar</code>	645, 647, 669, 670, 671
<code>\checkend</code>	138, 173, 213, 248, 294,
<code>\defaultsubs</code>	311, 335, 354, 426, 452, 523, 525
<code>\empty</code>	154, 193, 229, 268, 383, 407
<code>\filelist</code>	149, 187, 224, 262, 376, 399, 546, 552, 553
<code>\empty</code>	58, 59, 60, 61, 62, 80, 91, 102, 114, 126, 485, 600, 643
<code>\enddocumenthook</code>	137, 172, 212, 247, 334, 353
<code>\firstofone</code>	79, 90, 101, 113,

\AtVeryEnd@AtVeryEndDocumentHook	
.....	60, 70, 102, 106, 108
\@firstoftwo	53
\@font@warning	
.....	151, 190, 226, 265, 378, 402
\@gobble	606, 629, 685, 693
\@gobbletwo	
.	143, 152, 180, 191, 218, 227,
255, 266, 341, 362, 380, 404, 665	
\@ifpackageloaded	562, 570
\@ifundefined	545
\@latex@warning@no@line	
.....	159, 198, 234, 273, 387, 411
\@mainaux .	142, 179, 217, 254, 304,
323, 339, 360, 430, 458, 581, 586	
\@mainlbl	299, 318
\@mlabel	579, 605, 626, 653, 665
\@multiplelabels	
.....	157, 163, 196, 202, 232,
238, 271, 277, 385, 393, 409, 417	
\@namedef	431, 459
\@newl@bel	144, 181, 219, 256, 342, 363
\@nil	493, 504, 611, 618
\@onelevel@sanitize	602
\@outputdblcol	424, 450
\@partaux	340, 361
\@refundefined	
.....	155, 194, 230, 269, 347, 369
\@secondoftwo	55
\@setckpt .	143, 180, 218, 255, 341, 362
\@startlabels .	578, 581, 652, 660, 664
\@tempswafalse	145,
182, 220, 257, 343, 364, 434, 462	
\@testdef	144, 181, 219,
256, 342, 363, 432, 433, 460, 461	
\@undefined ..	86, 97, 108, 120, 132, 495
\@unexpandable@protect	625
\@warning	438, 466
\`	624, 754
\{	606, 677
\}	678
A	
\a@enddocument	518
\advance	718, 726, 741
\AfterEndDocument	572
\aftergroup	537
\AfterLastShipout .	2, 66, 90, 663, 788
\AfterReadingMainAux	567
\AP@enddocument	508
\AtBeginDocument ..	539, 561, 577, 651
\AtEndAfterFileList	3, 72, 113
\AtEndDocument	136, 171, 211,
246, 540, 544, 584, 628, 656, 787	
\AtVeryEnd@AfterLastShipoutHook .	
.....	59, 67, 91, 95, 97
\AtVeryEnd@AtEnd .	28, 29, 46, 592, 674
\AtVeryEnd@AtEndAfterFileListHook	61, 73, 114, 118, 120
B	
\balancing@outputdblcol .	424, 450
\BeforeClearDocument	2, 63, 79
\BeforeClosingMainAux	564
\bibcite	433, 461
\body	697, 701
C	
\c@labelgen	298, 317
\c@lenddoca	346, 368, 397
\c@lmainauxfile	344, 365
\Call@AfterLastShipout	89,
176, 251, 314, 357, 455, 533, 564	

\Call@AtEndAfterFileList	111, 124, 188, 263, 327, 400, 474, 548, 556	\hyper@fn@enddocument	511
\Call@AtVeryEndDocument 100, 112, 186, 261, 325, 367, 472, 547, 554, 567, 572	I	
\Call@AtVeryVeryEnd 123, 207, 282, 330, 372, 477	\if@filesw	141, 156, 178, 195, 216, 231, 253, 270, 297, 316, 338, 359, 384, 408, 429, 457, 580, 585
\Call@BeforeClearDocument 78, 174, 249, 312, 355, 453, 531	\if@lastpagebalancing	423, 449
\catcode	2, 3, 5, 6, 7, 11, 12, 13, 14, 15, 16, 17, 20, 21, 23, 24, 25, 26, 30, 32, 677, 678, 679, 680, 715, 724, 732, 736, 753, 754, 755	\if@tempswa	158, 197, 233, 272, 386, 410, 437, 465
\clearpage 139, 175, 214, 250, 302, 321, 336, 356, 427, 454, 528, 529, 530, 532, 586, 659, 789	\ifdim	150, 189, 225, 264, 377, 401
\closeout 142, 179, 217, 254, 299, 304, 318, 323, 339, 340, 360, 361, 430, 458	\ifnum	298, 317, 717, 725, 732, 740
\count@ 682, 711, 715, 717, 718, 722, 724, 725, 726, 730, 732, 735, 736, 740, 741	\ifx	52, 80, 91, 102, 114, 126, 157, 196, 232, 271, 385, 397, 409, 481, 495, 527, 590, 596, 600, 620, 641, 681, 684, 687, 690, 745
\countdef 682	\immediate	142, 179, 217, 254, 299, 304, 318, 323, 339, 340, 360, 361, 430, 458, 581, 586
\csname 9, 52, 210, 245, 326, 473, 481, 483, 596, 681, 684, 687, 690, 745, 772	\input	147, 184, 301, 320, 344, 365, 436, 464, 746
\cweb@save@enddocument 512	\iterate	698, 700, 702
D			
\deadcycles 167, 206, 242, 281, 307, 329, 349, 371, 445, 476	J	
\docmute@enddocument 517	\jobname	147, 184, 222, 259, 436, 464
E			
\EMenddocument 516	\jobname@lbl	301, 320
\end 773, 786	K	
\endcsname 9, 52, 210, 245, 326, 473, 481, 483, 596, 681, 684, 687, 690, 745, 772	\keependdoc	515
\enddocument 507	L	
\enddocumentasusual 519	\LoadCommand	746, 756
\endinput 46	\loop	696, 712, 723, 731
\endletter 621, 622, 638	M	
\endlinechar 4, 10, 22	\makeatletter	146, 183, 221, 258, 300, 319, 344, 365, 435, 463
\endorigdocument 514	\makelabels	590, 650
\errmessage 734	\MessageBreak	151, 190, 226, 265, 379, 403, 646, 669, 670
F			
\font@submax	150, 152, 189, 191, 225, 227, 264, 266, 377, 380, 401, 404	\mlabel	579, 653
\fontsubfuzz	150, 189, 225, 264, 377, 401	N	
G			
\g@addto@macro 64, 67, 70, 73, 76	\NeedsTeXFormat	47
\gdef 546	\newcommand	63, 66, 69, 72, 75, 78, 89, 100, 111, 123
H			
\hyper@back@cite@enddocument 509	\newlabel	432, 460
\hyper@enddocument 510	\newpage	295, 313
I			
\if@filesw	141, 156, 178, 195, 216, 231, 253, 270, 297, 316, 338, 359, 384, 408, 429, 457, 580, 585	\next	702, 704, 706
\if@lastpagebalancing	423, 449	\number	737
\if@tempswa	158, 197, 233, 272, 386, 410, 437, 465	O	
\ifdim	150, 189, 225, 264, 377, 401	\old@enddocument	520
\ifnum	298, 317, 717, 725, 732, 740	\on@line	485, 643
P			
\PackageInfo	... 81, 83, 92, 94, 103, 105, 115, 117, 127, 129, 486, 644	\PackageWarningNoLine	668
\PackageWarningNoLine 668	\prev@enddocument	513
\protect 625	\providepackage	48

R	\the 10, 11, 12, 13, 14, 15, 16, 17, 30, 555, 715, 735, 736
\RangeCatcodeCheck 729, 757, 758, 759, 760, 761, 762, 763, 764, 765, 766, 767, 768
\RangeCatcodeInvalid	721, 749, 750, 751, 752
\repeat	696, 708, 719, 727, 742
\RestoreCatcodes	710, 713, 714, 769
S	
\space	152, 191, 227, 266, 380, 404, 735, 736, 744
\startlabels	578, 652
T	
\Test	748, 771
\the	10, 11, 12, 13, 14, 15, 16, 17, 30, 555, 715, 735, 736
\TMP@EnsureCode	27, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45
\toks@	552, 555
\twoclearpage	290
\twoupclearpage	286
W	
\write	581, 586
X	
\x	8, 20, 627, 632
Z	
\z@	167, 206, 242, 281, 307, 317, 329, 349, 371, 445, 476