

The `letltxmacro` package

Heiko Oberdiek*
<heiko.oberdiek at googlemail.com>

2016/05/16 v1.5

Abstract

\TeX 's `\let` assignment does not work for \LaTeX macros with optional arguments or for macros that are defined as robust macros by `\DeclareRobustCommand`. This package defines `\LetLtxMacro` that also takes care of the involved internal macros.

Contents

1 Documentation	2
1.1 Supported macro definition commands	2
2 Implementation	2
2.1 Show cases	2
2.1.1 <code>letltxmacro-showcases.tex</code>	2
2.1.2 Result	4
2.2 Package	5
2.2.1 Catcodes and identification	5
2.2.2 Main macros	6
3 Test	8
3.1 Catcode checks for loading	8
3.2 Package tests	9
4 Installation	13
4.1 Download	13
4.2 Bundle installation	13
4.3 Package installation	14
4.4 Refresh file name databases	14
4.5 Some details for the interested	14
5 Catalogue	15
6 History	15
[2008/06/09 v1.0]	15
[2008/06/12 v1.1]	16
[2008/06/13 v1.2]	16
[2008/06/24 v1.3]	16
[2010/09/02 v1.4]	16
[2016/05/16 v1.5]	16

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1 Documentation

If someone wants to redefine a macro with using the old meaning, then one method is TeX's command \let:

```
\newcommand{\Macro}{\typeout{Test Macro}}
\let\SavedMacro=\Macro
\renewcommand{\Macro}{%
  \typeout{Begin}%
  \SavedMacro
  \typeout{End}%
}
```

However, this method fails, if \Macro is defined by \DeclareRobustCommand and/or has an optional argument. In both cases LATEX defines an additional internal macro that is forgotten in the simple \let assignment of the example above.

\LetLtxMacro {\langle new macro \rangle} {\langle old macro \rangle}
--

Macro \LetLtxMacro behaves similar to TeX's \let assignment, but it takes care of macros that are defined by \DeclareRobustCommand and/or have optional arguments. Example:

```
\DeclareRobustCommand{\Macro}[1][default]{...}
\LetLtxMacro{\SavedMacro}{\Macro}
```

Then macro \SavedMacro only uses internal macro names that are derived from \SavedMacro's macro name. Macro \Macro can now be redefined without affecting \SavedMacro.

\GlobalLetLtxMacro {\langle new macro \rangle} {\langle old macro \rangle}
--

Like \LetLtxMacro, but the \langle new macro \rangle is defined globally. Since version 2016/05/16 v1.4.

1.1 Supported macro definition commands

\newcommand, \renewcommand	latex/base
\newenvironment, \renewenvironment	latex/base
\DeclareRobustCommand	latex/base
\newrobustcmd, \renewrobustcmd	etoolbox
\robustify	etoolbox 2008/06/22 v1.6

2 Implementation

2.1 Show cases

2.1.1 letltxmacro-showcases.tex

```
1 /*showcases*/
2 \NeedsTeXFormat{LaTeX2e}
3 \makeatletter
```

\Line The result is displayed by macro \Line. The percent symbol at line start allows easy grepping and inserting into the DTX file.

```

4 \newcommand*{\Line}[1]{%
5   \typeout{@percentchar#1}%
6 }

7 \newcommand*{\ShowCmdName}[1]{%
8   @ifundefined{#1}{\Line{}}{%
9     \Line{%
10       \space\space(\expandafter\string\csname#1\endcsname) = %
11       (\expandafter\meaning\csname#1\endcsname)}%
12   }%
13 }%
14 }
15 \newcommand*{\ShowCmds}[1]{%
16   \ShowCmdName{#1}%
17   \ShowCmdName{#1}%
18   \ShowCmdName{\#1}%
19   \ShowCmdName{\#1}%
20 }
21 \let\\@backslashchar

\ShowDef
22 \newcommand*{\ShowDef}[2]{%
23   \begingroup
24   \Line{}%
25   \newcommand*{\DefString}{#2}%
26   \onelevel@sanitize\DefString
27   \Line{\DefString}%
28   #2%
29   \ShowCmds{#1}%
30   \endgroup
31 }

32 \typeout{}
33 \Line{* LaTeX definitions:}
34 \ShowDef{cmd}{%
35   \newcommand{\cmd}[2][default]{}%
36 }
37 \ShowDef{cmd}{%
38   \DeclareRobustCommand{\cmd}{}%
39 }
40 \ShowDef{cmd}{%
41   \DeclareRobustCommand{\cmd}[2][default]{}%
42 }
43 \typeout{}

```

The minimal version of package etoolbox is 2008/06/12 v1.6a because it fixes \robustify.

```

44 \RequirePackage{etoolbox}[2008/06/12]%
45 \Line{%
46 \Line{* etoolbox's robust definitions:}
47 \ShowDef{cmd}{%
48   \newrobustcmd{\cmd}{}%
49 }
50 \ShowDef{cmd}{%
51   \newrobustcmd{\cmd}[2][default]{}%
52 }

```

```

53 \Line{ }
54 \Line{* etoolbox's string\robustify:}
55 \ShowDef{cmd}{%
56   \newcommand{\cmd}[2][default]{} %
57   \robustify{\cmd}%
58 }
59 \ShowDef{cmd}{%
60   \DeclareRobustCommand{\cmd}{} %
61   \robustify{\cmd}%
62 }
63 \ShowDef{cmd}{%
64   \DeclareRobustCommand{\cmd}[2][default]{} %
65   \robustify{\cmd}%
66 }
67 \typeout{ }
68 \@@end
69 
```

2.1.2 Result

* LaTeX definitions:

```
\newcommand {\cmd }[2][default]{}
(\cmd ) = (macro:->\@protected@testopt \cmd \\cmd {default})
(\cmd ) = (\long macro:[#1]#2->)
```

```
\DeclareRobustCommand {\cmd }{%
(\cmd ) = (macro:->\protect \cmd_ )
(\cmd_ ) = (\long macro:->)
```

```
\DeclareRobustCommand {\cmd }[2][default]{%
(\cmd ) = (macro:->\protect \cmd_ )
(\cmd_ ) = (macro:->\@protected@testopt \cmd_ \\cmd_ {default})
(\cmd_ ) = (\long macro:[#1]#2->)
```

* etoolbox's robust definitions:

```
\newrobustcmd {\cmd }{%
(\cmd ) = (\protected\long macro:->)
```

```
\newrobustcmd {\cmd }[2][default]{%
(\cmd ) = (\protected macro:->\@testopt \cmd {default})
(\cmd ) = (\long macro:[#1]#2->)
```

* etoolbox's \robustify:

```
\newcommand {\cmd }[2][default]{} \robustify {\cmd }
(\cmd ) = (\protected macro:->\@protected@testopt \cmd \\cmd {default})
(\cmd ) = (\long macro:[#1]#2->)
```

```
\DeclareRobustCommand {\cmd }{} \robustify {\cmd }
(\cmd ) = (\protected macro:->)
```

```
\DeclareRobustCommand {\cmd }[2][default]{} \robustify {\cmd }
(\cmd ) = (\protected macro:->\@protected@testopt \cmd_ \\cmd_ {default})
(\cmd_ ) = (macro:->\@protected@testopt \cmd_ \\cmd_ {default})
(\cmd_ ) = (\long macro:[#1]#2->)
```

2.2 Package

70 /*package)

2.2.1 Catcodes and identification

```
71 \begingroup\catcode61\catcode48\catcode32=10\relax%
72   \catcode13=5 % ^~M
73   \endlinechar=13 %
74   \catcode123=1 %
75   \catcode125=2 %
76   \catcode64=11 %
77   \def\x{\endgroup
78   \expandafter\edef\csname l1m@AtEnd\endcsname{%
79     \endlinechar=\the\endlinechar\relax
80     \catcode13=\the\catcode13\relax
81     \catcode32=\the\catcode32\relax
82     \catcode35=\the\catcode35\relax
83     \catcode61=\the\catcode61\relax
84     \catcode64=\the\catcode64\relax
85     \catcode123=\the\catcode123\relax
86     \catcode125=\the\catcode125\relax
87   }%
88 }%
89 \x\catcode61\catcode48\catcode32=10\relax%
90 \catcode13=5 % ^~M
91 \endlinechar=13 %
92 \catcode35=6 %
93 \catcode64=11 %
94 \catcode123=1 %
95 \catcode125=2 %
96 \def\TMP@EnsureCode#1#2{%
97   \edef\l1m@AtEnd{%
98     \l1m@AtEnd
99     \catcode#1=\the\catcode#1\relax
100   }%
101   \catcode#1=#2\relax
102 }
103 \TMP@EnsureCode{40}{12}%
104 \TMP@EnsureCode{41}{12}%
105 \TMP@EnsureCode{42}{12}%
106 \TMP@EnsureCode{45}{12}%
107 \TMP@EnsureCode{46}{12}%
108 \TMP@EnsureCode{47}{12}%
109 \TMP@EnsureCode{58}{12}%
110 \TMP@EnsureCode{62}{12}%
111 \TMP@EnsureCode{91}{12}%
112 \TMP@EnsureCode{93}{12}%
113 \edef\l1m@AtEnd{%
114   \l1m@AtEnd
115   \escapechar\the\escapechar\relax
116   \noexpand\endinput
117 }
118 \escapechar=92 % '\\
119 \NeedsTeXFormat{LaTeX2e}
120 \ProvidesPackage{letltxmacro}%
121   [2016/05/16 v1.5 Let assignment for LaTeX macros (HO)]
```

2.2.2 Main macros

```

\LetLtxMacro
122 \newcommand*\{\\LetLtxMacro}{%
123   \\llm@ModeLetLtxMacro{}%
124 }

\GlobalLetLtxMacro
125 \newcommand*\{\\GlobalLetLtxMacro}{%
126   \\llm@ModeLetLtxMacro\\global
127 }

\\llm@ModeLetLtxMacro
128 \newcommand*\{\\llm@ModeLetLtxMacro}[3]{%
129   \\edef\\llm@escapechar{\\the\\escapechar}{%
130     \\escapechar=-1 %
131   \\edef\\reserved@a{%
132     \\noexpand\\protect
133     \\expandafter\\noexpand
134     \\csname\\string#3 \\endcsname
135   }%
136   \\ifx\\reserved@a#3\\relax
137     #1\\edef#2{%
138       \\noexpand\\protect
139       \\expandafter\\noexpand
140       \\csname\\string#2 \\endcsname
141     }%
142     #1\\expandafter\\let
143     \\csname\\string#2 \\expandafter\\endcsname
144     \\csname\\string#3 \\endcsname
145     \\expandafter\\llm@LetLtxMacro
146       \\csname\\string#2 \\expandafter\\endcsname
147       \\csname\\string#3 \\endcsname{#1}%
148   \\else
149     \\llm@LetLtxMacro{#2}{#3}{#1}%
150   \\fi
151   \\escapechar=\\llm@escapechar\\relax
152 }

\\llm@LetLtxMacro
153 \\def\\llm@LetLtxMacro#1#2#3{%
154   \\escapechar=92 %
155   \\expandafter\\llm@CheckParams\\meaning#2:->\\nil{%
156     \\begingroup
157       \\def\\@protected@testopt{%
158         \\expandafter\\@testopt\\@gobble
159       }%
160       \\def\\@testopt##1##2{%
161         \\toks@={##2}%
162       }%
163       \\let\\llm@testopt\\empty
164       \\edef\\x{%
165         \\noexpand\\@protected@testopt
166         \\noexpand#2%
167         \\expandafter\\noexpand\\csname\\string#2\\endcsname
168       }%
169       \\expandafter\\expandafter\\expandafter\\def
170       \\expandafter\\expandafter\\expandafter\\y

```

```

171      \expandafter\expandafter\expandafter{%
172          \expandafter\llm@CarThree#2{}{}\llm@nil
173      }%
174      \ifx\x\y
175          #2%
176          \def\llm@testopt{%
177              \noexpand\@protected@testopt
178              \noexpand#1%
179          }%
180      \else
181          \edef\x{%
182              \noexpand\@testopt
183              \expandafter\noexpand
184              \csname\string#2\endcsname
185          }%
186          \expandafter\expandafter\expandafter\def
187          \expandafter\expandafter\expandafter\y
188          \expandafter\expandafter\expandafter{%
189              \expandafter\llm@CarTwo#2{}{}\llm@nil
190          }%
191          \ifx\x\y
192              #2%
193              \def\llm@testopt{%
194                  \noexpand\@testopt
195              }%
196          \fi
197      \fi
198      \ifx\llm@testopt\@empty
199      \else
200          \llm@protected\xdef\llm@GlobalTemp{%
201              \llm@testopt
202              \expandafter\noexpand
203              \csname\string#1\endcsname
204              {\the\toks@}%
205          }%
206      \fi
207      \expandafter\endgroup\ifx\llm@testopt\@empty
208          #3\let#1=#2\relax
209      \else
210          #3\let#1=\llm@GlobalTemp
211          #3\expandafter\let
212              \csname\string#1\expandafter\endcsname
213              \csname\string#2\endcsname
214          \fi
215      }%
216      #3\let#1=#2\relax
217  }%
218 }

\llm@CheckParams

219 \def\llm@CheckParams#1:->#2\@nil{%
220     \begingroup
221     \def\x{\#1}%
222     \ifx\x\llm@macro
223         \endgroup
224         \def\llm@protected{}%
225         \expandafter\@firstoftwo
226     \else

```

```

227   \ifx\x\llm@protectedmacro
228     \endgroup
229     \def\llm@protected{\protected}%
230     \expandafter\expandafter\expandafter\@firstoftwo
231   \else
232     \endgroup
233     \expandafter\expandafter\expandafter\@secondoftwo
234   \fi
235 \fi
236 }

\llm@macro
237 \def\llm@macro{macro}
238 @onelvel@sanitize\llm@macro

\llm@protectedmacro
239 \def\llm@protectedmacro{\protected macro}
240 @onelvel@sanitize\llm@protectedmacro

\llm@CarThree
241 \def\llm@CarThree#1#2#3#4\llm@nil{#1#2#3}%

\llm@CarTwo
242 \def\llm@CarTwo#1#2#3\llm@nil{#1#2}%

243 \llm@AtEnd%
244 </package>

```

3 Test

3.1 Catcode checks for loading

```

245 <*test1>
246 \NeedsTeXFormat{LaTeX2e}
247 \documentclass{minimal}
248 \makeatletter
249 \def\RestoreCatcodes{}
250 \count@=0 %
251 \loop
252   \edef\RestoreCatcodes{%
253     \RestoreCatcodes
254     \catcode\the\count@=\the\catcode\count@\relax
255   }%
256 \ifnum\count@<255 %
257   \advance\count@\@ne
258 \repeat
259
260 \def\RangeCatcodeInvalid#1#2{%
261   \count@=#1\relax
262   \loop
263     \catcode\count@=15 %
264   \ifnum\count@<#2\relax
265     \advance\count@\@ne
266   \repeat
267 }
268 \def\Test{%
269   \RangeCatcodeInvalid{0}{47}%

```

```

270 \RangeCatcodeInvalid{58}{64}%
271 \RangeCatcodeInvalid{91}{96}%
272 \RangeCatcodeInvalid{123}{127}%
273 \catcode`\@=12 %
274 \catcode`\\=0 %
275 \catcode`\#=1 %
276 \catcode`\}=2 %
277 \catcode`\#=6 %
278 \catcode`\[=12 %
279 \catcode`\]=12 %
280 \catcode`\%=14 %
281 \catcode`\ =10 %
282 \catcode`13=5 %
283 \RequirePackage{letltxmacro}[2016/05/16]\relax
284 \RestoreCatcodes
285 }
286 \Test
287 \csname @@end\endcsname
288 \end
289 </test1>

```

3.2 Package tests

```

290 <*test2>
291 \NeedsTeXFormat{LaTeX2e}
292 \nofiles
293 \documentclass{minimal}
294
295 \usepackage{letltxmacro}[2016/05/16]
296
297 \usepackage{qstest}
298 \IncludeTests{*}
299 \LogTests{log}{*}{*}
300
301 \makeatletter
302
303 \def\TestDef#1{%
304   \begingroup
305     \makeother\\%
306     \makeother\ %
307     \expandafter\@TestDef\csname #1\endcsname
308 }
309 \def\@TestDef#1#2{%
310   \edef\@a{\expandafter\strip@prefix\meaning#1}%
311   \edef\@b{\detokenize{#2}}%
312   \ifx\@a\@b
313     \else
314       \typeout{1 [\@a]}%
315       \typeout{2 [\@b]}%
316     \fi
317   \endgroup
318   \Expect*\expandafter\strip@prefix\meaning#1*\detokenize{#2}%
319 }
320 \def\TestEquals#1#2{%
321   \Expect*%
322   \expandafter\ifx\csname#1\expandafter\endcsname
323                           \csname#2\endcsname
324     equals%

```

```

325     \else
326         wrong%
327     \fi
328 }{equals}%
329 }
330 \def\SaveA{%
331   \let\SavedA\TestA
332   \expandafter\let\csname string\SavedA\expandafter\endcsname
333   \csname string\TestA\endcsname
334   \expandafter\let\csname SavedA \expandafter\endcsname
335   \csname TestA \endcsname
336 }
337 \def\CheckA{%
338   \TestEquals{SavedA}{TestA}%
339   \TestEquals{\string\SavedA}{\string\TestA}%
340   \TestEquals{SavedA }{TestA }%
341 }
342
343 \begin{qstest}{robust}{robust}
344   \begingroup
345     \DeclareRobustCommand*\TestA{Test}%
346     \SaveA
347     \TestDef{TestA}{\protect \TestA }%
348     \CheckA
349     \DeclareRobustCommand{\TestA}{Test}%
350     \SaveA
351     \TestDef{TestA}{\protect \TestA }%
352     \LetLtxMacro\TestB\TestA
353     \TestDef{TestB}{\protect \TestB }%
354     \TestEquals{TestB }{TestA }%
355     \CheckA
356     \GlobalLetLtxMacro\TestC\TestA
357     \CheckA
358   \endgroup
359   \TestDef{TestC}{\protect \TestC }%
360   \DeclareRobustCommand{\TestA}{Test}%
361   \TestEquals{TestC }{TestA }%
362 \end{qstest}
363
364 \begin{qstest}{default}{default}
365   \begingroup
366     \newcommand{\TestA}[1][\relax default \empty]{\TestA #1}%
367     \SaveA
368     \TestDef
369     {\TestA}{\@protected@testopt \TestA \\ \TestA {\relax default \empty}}%
370     \LetLtxMacro\TestB\TestA
371     \TestDef
372     {\TestB}{\@protected@testopt \TestB \\ \TestB {\relax default \empty}}%
373     \CheckA
374     \TestEquals{\string\TestB}{\string\TestA}%
375     \GlobalLetLtxMacro\TestC\TestA
376     \CheckA
377   \endgroup
378   \TestDef
379   {\TestC}{\@protected@testopt \TestC \\ \TestC {\relax default \empty}}%
380   \newcommand{\TestA}[1][\relax default \empty]{\TestA #1}%
381   \TestEquals{\string\TestC}{\string\TestA}%
382 \end{qstest}

```

```

383
384 \begin{qstest}{robustdefault}{robustdefault}
385   \begingroup
386     \DeclareRobustCommand{\TestA}[1][\default]{\TestA}%
387     \SaveA
388     \LetLtxMacro{\TestB}{\TestA}
389     \TestDef{\TestB}{\protect \TestB }%
390     \TestDef{\TestB }{\@protected@testopt \TestB \\ \TestB {\default }}%
391     \CheckA
392     \GlobalLetLtxMacro{\TestC}{\TestA}
393     \CheckA
394   \endgroup
395   \TestDef{\TestC}{\protect \TestC }%
396   \TestDef{\TestC }{\@protected@testopt \TestC \\ \TestC {\default }}%
397 \end{qstest}
398
399 \begin{qstest}{plain}{plain}
400   \LetLtxMacro{\NewRelax}{\relax}
401   \Expect*{\meaning\relax}{\string\relax}%
402   \Expect*{\meaning\NewRelax}{\string\relax}%
403   \LetLtxMacro{\NewHbox}{\hbox}
404   \Expect*{\meaning\hbox}{\string\hbox}%
405   \Expect*{\meaning\NewHbox}{\string\hbox}%
406   \LetLtxMacro{\NewEmpty}{\empty}
407   \Expect*{\meaning\empty}{macro:->}%
408   \Expect*{\meaning\NewEmpty}{macro:->}%
409   \def{\TestA{\iffalse}}%
410   \LetLtxMacro{\TestB}{\TestA}
411   \TestDef{\TestB}{\iffalse }%
412   \TestEquals{\TestA}{\TestB}%
413 \end{qstest}
414 \usepackage{etoolbox}[2008/06/22]
415
416 \begin{qstest}{oldnewrobustcmd}{oldnewrobustcmd}
417   \begingroup
418     \protected\edef{\TestA}{%
419       \noexpand\@protected@testopt
420       \noexpand\TestA
421       \expandafter\noexpand\csname\string\TestA\endcsname
422       {\noexpand\default}%
423     }%
424     \expandafter\protected\expandafter
425     \def{\csname\string\TestA\endcsname{\TestA}}%
426     \SaveA
427     \LetLtxMacro{\TestB}{\TestA}
428     \TestDef{\TestB}{\@protected@testopt \TestB \\ \TestB {\default }}%
429     \protected\edef{\TestC}{%
430       \noexpand\@protected@testopt
431       \noexpand\TestB
432       \expandafter\noexpand\csname\string\TestB\endcsname
433       {\noexpand\default}%
434     }%
435     \TestEquals{\TestB}{\TestC}%
436     \CheckA
437     \GlobalLetLtxMacro{\TestD}{\TestA}
438     \CheckA
439   \endgroup
440   \TestDef{\TestD}{\@protected@testopt \TestD \\ \TestD {\default }}%

```

```

441   \protected\edef\TestC{%
442     \noexpand\@protected@testopt
443     \noexpand\TestD
444     \expandafter\noexpand\csname\string\TestD\endcsname
445     {\noexpand\default}%
446   }%
447   \TestEquals{TestD}{TestC}%
448 \end{qstest}
449
450 \begin{qstest}{newrobustcmd}{newrobustcmd}
451   \begingroup
452     \newrobustcmd{\TestA}[1][\default]{TestA}%
453     \SaveA
454     \LetLtxMacro{\TestB}{\TestA}
455     \TestDef{\TestB}{\@testopt \\TestB {\default}}%
456     \protected\edef\TestC{%
457       \noexpand\@testopt
458       \expandafter\noexpand\csname\string\TestB\endcsname
459       {\noexpand\default}%
460     }%
461     \TestEquals{TestB}{TestC}%
462     \CheckA
463     \GlobalLetLtxMacro{\TestD}{\TestA}
464     \CheckA
465   \endgroup
466   \TestDef{\TestD}{\@testopt \\TestD {\default}}%
467   \protected\edef\TestC{%
468     \noexpand\@testopt
469     \expandafter\noexpand\csname\string\TestD\endcsname
470     {\noexpand\default}%
471   }%
472   \TestEquals{TestD}{TestC}%
473 \end{qstest}
474
475 \begin{qstest}{robustifyopt}{robustifyopt}
476   \newcommand{\TestA}[2][\default]{}
477   \TestDef{\TestA}{\@protected@testopt \TestA \\TestA {\default}}%
478   \robustify{\TestA}
479   \TestDef{\TestA}{\@protected@testopt \TestA \\TestA {\default}}%
480   \protected\edef\TestC{%
481     \noexpand\@protected@testopt
482     \noexpand\TestA
483     \expandafter\noexpand\csname\string\TestA\endcsname
484     {\noexpand\default}%
485   }%
486   \TestEquals{TestA}{TestC}%
487   \SaveA
488   \LetLtxMacro{\TestB}{\TestA}
489   \TestDef{\TestB}{\@protected@testopt \TestB \\TestB {\default}}%
490   \protected\edef\TestC{%
491     \noexpand\@protected@testopt
492     \noexpand\TestB
493     \expandafter\noexpand\csname\string\TestB\endcsname
494     {\noexpand\default}%
495   }%
496   \TestEquals{TestB}{TestC}%
497   \CheckA
498 \end{qstest}

```

```

499
500 \begin{qstest}{robustifydeclare}{robustifydeclare}
501   \DeclareRobustCommand{\TestA}{\iffalse}%
502   \robustify{\TestA}
503   \SaveA
504   \LetLtxMacro{\TestB}{\TestA}
505   \TestDef{\TestB}{\iffalse }%
506   % before etoolbox 2008/06/22: \protected\long\def
507   % since etoolbox 2008/06/22: \protected\def
508   \protected\def{\TestC}{\iffalse}%
509   \TestEquals{\TestB}{\TestC}%
510   \CheckA
511 \end{qstest}
512
513 \begin{qstest}{robustifydeclarelong}{robustifydeclarelong}
514   \DeclareRobustCommand{\TestA[1]}{\iffalse}%
515   \robustify{\TestA}
516   \SaveA
517   \LetLtxMacro{\TestB}{\TestA}
518   \TestDef{\TestB}{\iffalse }%
519   % before etoolbox 2008/06/22: \protected\long\def
520   % since etoolbox 2008/06/22: \protected\def
521   \protected\long\def{\TestC#1}{\iffalse}%
522   \TestEquals{\TestB}{\TestC}%
523   \CheckA
524 \end{qstest}
525 \csname @@end\endcsname
526 </test2>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/letltxmacro.dtx](http://ctan.org/pkg/letltxmacro) The source file.

[CTAN:macros/latex/contrib/oberdiek/letltxmacro.pdf](http://ctan.org/pkg/letltxmacro) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](http://ctan.org/pkg/oberdiek)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](http://ctan.org/pkg/tds)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

`unzip oberdiek.tds.zip -d ~/texmf`

¹<http://ctan.org/pkg/letltxmacro>

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TEX`:

```
tex letltxmacro.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>letltxmacro.sty</code>	→ <code>tex/latex/oberdiek/letltxmacro.sty</code>
<code>letltxmacro.pdf</code>	→ <code>doc/latex/oberdiek/letltxmacro.pdf</code>
<code>letltxmacro-showcases.tex</code>	→ <code>doc/latex/oberdiek/letltxmacro-showcases.tex</code>
<code>test/letltxmacro-test1.tex</code>	→ <code>doc/latex/oberdiek/test/letltxmacro-test1.tex</code>
<code>test/letltxmacro-test2.tex</code>	→ <code>doc/latex/oberdiek/test/letltxmacro-test2.tex</code>
<code>letltxmacro.dtx</code>	→ <code>source/latex/oberdiek/letltxmacro.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TEX` distribution (`teTEX`, `mikTEX`, ...) relies on file name databases, you must refresh these. For example, `teTEX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk letltxmacro.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{letltxmacro.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdflAT_EX:

```
pdflatex letltxmacro.dtx
makeindex -s gind.ist letltxmacro.idx
pdflatex letltxmacro.dtx
makeindex -s gind.ist letltxmacro.idx
pdflatex letltxmacro.dtx
```

5 Catalogue

The following XML file can be used as source for the [TeX Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `letltxmacro.xml`.

```
527 <catalogue>
528 <?xml version='1.0' encoding='us-ascii'?>
529 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
530 <entry datestamp='$Date$' modifier='$Author$' id='letltxmacro'>
531   <name>letltxmacro</name>
532   <caption>Let assignment for LaTeX macros.</caption>
533   <authorref id='auth:oberdiek' />
534   <copyright owner='Heiko Oberdiek' year='2008,2010' />
535   <license type='lppl1.3' />
536   <version number='1.5' />
537   <description>
538     TeX&#x2019;s <tt>\let</tt> assignment does not work for LaTeX macros
539     with optional arguments or for macros that are defined
540     as robust macros by <tt>\DeclareRobustCommand</tt>. This package
541     defines <tt>\LetLtxMacro</tt> that also takes care of the involved
542     internal macros.
543   <p/>
544   The package is part of the <xref refid='oberdiek'>oberdiek</xref>
545   bundle.
546 </description>
547 <documentation details='Package documentation'
548   href='ctan:/macros/latex/contrib/oberdiek/letltxmacro.pdf' />
549 <ctan file='true' path='/macros/latex/contrib/oberdiek/letltxmacro.dtx' />
550 <miktex location='oberdiek' />
551 <texlive location='oberdiek' />
552 <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
553 </entry>
554 </catalogue>
```

6 History

[2008/06/09 v1.0]

- First version.

[2008/06/12 v1.1]

- Support for etoolbox's \newrobustcmd added.

[2008/06/13 v1.2]

- Support for etoolbox's \robustify added.

[2008/06/24 v1.3]

- Test file adapted for etoolbox 2008/06/22 v1.6.

[2010/09/02 v1.4]

- \GlobalLetLtxMacro added.

[2016/05/16 v1.5]

- Documentation updates.

7 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
\#	277
\%	280
\@	273
\@end	68
\@TestDef	307, 309
\@backslashchar	21
\@empty	163, 198, 207
\@firstoftwo	225, 230
\@gobble	158
\@ifundefined	8
\@makeother	305, 306
\@ne	257, 265
\@nil	155, 219
\@onelevel@sanitize	26, 238, 240
\@percentchar	5
\@protected@testopt	157, 165, 177, 369, 372, 379, 390, 396, 419, 428, 430, 440, 442, 477, 479, 481, 489, 491
\@secondoftwo	233
\@testopt	158, 160, 182, 194, 455, 457, 466, 468
\[.	278
\\"	18, 19, 21, 118, 274, 305, 369, 372, 379, 390, 396, 428, 440, 455, 466, 477, 479, 489
\{	275
\}	276
\]	279
_	281, 306
\a	310, 312, 314
\advance	257, 265
\b	311, 312, 315
\begin	343, 364, 384, 399, 416, 450, 475, 500, 513
\catcode	71, 72, 74, 75, 76, 80, 81, 82, 83, 84, 85, 86, 89, 90, 92, 93, 94, 95, 99, 101, 254, 263, 273, 274, 275, 276, 277, 278, 279, 280, 281, 282
\CheckA	337, 348, 355, 357, 373, 376, 391, 393, 436, 438, 462, 464, 497, 510, 523
\cmd	35, 38, 41, 48, 51, 56, 57, 60, 61, 64, 65
\count@	250, 254, 256, 257, 261, 263, 264, 265
\csname	10, 11, 78, 134, 140, 143, 144, 146, 147, 167, 184, 203, 212, 213, 287, 307, 322, 323, 332, 333, 334, 335, 421, 425, 432, 444, 458, 469, 483, 493, 525

	D	
\DeclareRobustCommand .	38, 41, 60, 64, 345, 349, 360, 386, 501, 514, 540	
\default .	386, 390, 396, 422, 428, 433, 440, 445, 452, 455, 459, 466, 470, 476, 477, 479, 484, 489, 494	
\DefString .	25, 26, 27	
\detokenize .	311, 318	
\documentclass .	247, 293	
	E	
\empty .	366, 369, 372, 379, 380, 406, 407	
\end .	288, 362, 382, 397, 413, 448, 473, 498, 511, 524	
\endcsname .	10, 11, 78, 134, 140, 143, 144, 146, 147, 167, 184, 203, 212, 213, 287, 307, 322, 323, 332, 333, 334, 335, 421, 425, 432, 444, 458, 469, 483, 493, 525	
\endinput .	116	
\endlinechar .	73, 79, 91	
\escapechar .	115, 118, 129, 130, 151, 154	
\Expect .	318, 321, 401, 402, 404, 405, 407, 408	
	G	
\GlobalLetLtxMacro 2, <u>125</u> , 356, 375, 392, 437, 463	
	H	
\hbox .	403, 404, 405	
	I	
\iffalse .	409, 411, 501, 505, 508, 514, 518, 521	
\ifnum .	256, 264	
\ifx .	136, 174, 191, 198, 207, 222, 227, 312, 322	
\IncludeTests .	298	
	L	
\LetLtxMacro .	2, <u>122</u> , 352, 370, 388, 400, 403, 406, 410, 427, 454, 488, 504, 517, 541	
\Line .	4, 9, 24, 27, 33, 45, 46, 53, 54	
\llm@AtEnd .	97, 98, 113, 114, 243	
\llm@CarThree .	172, <u>241</u>	
\llm@CarTwo .	189, <u>242</u>	
\llm@CheckParams .	155, <u>219</u>	
\llm@escapechar .	129, <u>151</u>	
\llm@GlobalTemp .	200, 210	
\llm@LetLtxMacro .	145, 149, <u>153</u>	
\llm@macro .	222, <u>237</u>	
\llm@ModeLetLtxMacro .	123, 126, <u>128</u>	
\llm@nil .	172, 189, 241, 242	
\llm@protected .	200, 224, 229	
\llm@protectedmacro .	227, <u>239</u>	
\llm@testopt .	163, 176, 193, 198, 201, 207	
\LogTests .	299	
	M	
\loop .	251, 262	
	N	
\NeedsTeXFormat .	2, 119, 246, 291	
\newcommand .	4, 7, 15, 22, 25, 35, 56, 122, 125, 128, 366, 380, 476	
\NewEmpty .	406, 408	
\NewHbox .	403, 405	
\NewRelax .	400, 402	
\newrobustcmd .	48, 51, 452	
\nofiles .	292	
	P	
\protect .	132, 138, 347, 351, 353, 359, 389, 395	
\protected .	229, 239, 418, 424, 429, 441, 456, 467, 480, 490, 506, 507, 508, 519, 520, 521	
\ProvidesPackage .	120	
	R	
\RangeCatcodeInvalid 260, 269, 270, 271, 272	
\repeat .	258, 266	
\RequirePackage .	44, 283	
\reserved@a .	131, 136	
\RestoreCatcodes .	249, 252, 253, 284	
\robustify .	54, 57, 61, 65, 478, 502, 515	
	S	
\SaveA .	330, 346, 350, 367, 387, 426, 453, 487, 503, 516	
\SavedA .	331, 332, 339	
\ShowCmdName .	7, 16, 17, 18, 19	
\ShowCmds .	15, 29	
\ShowDef .	22, 34, 37, 40, 47, 50, 55, 59, 63	
\space .	10	
\strip@prefix .	310, 318	
	T	
\Test .	268, 286	
\TestA .	331, 333, 339, 345, 347, 349, 351, 352, 356, 360, 366, 369, 370, 374, 375, 380, 381, 386, 388, 392, 409, 410, 418, 420, 421, 425, 427, 437, 452, 454, 463, 476, 477, 478, 479, 482, 483, 488, 501, 502, 504, 514, 515, 517	
\TestB .	352, 353, 370, 372, 374, 388, 389, 390, 410, 427, 428, 431, 432, 454, 458, 488, 489, 492, 493, 504, 517	

\TestC 356, 359, 375, \TMP@EnsureCode . 96, 103, 104, 105,
379, 381, 392, 395, 396, 429, 106, 107, 108, 109, 110, 111, 112
441, 456, 467, 480, 490, 508, 521 \toks@ 161, 204
\TestD 437, 440, 443, 444, 463, 469 \typeout 5, 32, 43, 67, 314, 315
\TestDef 303, 347, 351, \usepackage 295, 297, 414
353, 359, 368, 371, 378, 389,
390, 395, 396, 411, 428, 440,
455, 466, 477, 479, 489, 505, 518 \x 77, 89, 164, 174, 181, 191, 221, 222, 227
\TestEquals 320, 338, 339, 340, \y 170, 174, 187, 191
354, 361, 374, 381, 412, 435,
447, 461, 472, 486, 496, 509, 522
\the 79, 80, 81, 82,
83, 84, 85, 86, 99, 115, 129, 204, 254 \X
Y